

Abstract

This document provides references to the technical material that helps in developing applications on Microchip's 32-bit microcontroller units (MCUs).

Table of Contents

Abs	stract	1
1.	Cortex M0+ Family of Devices	3 8
2.	Cortex M23 Family of Devices 2.1. PIC32CM LE00/LS00/LS60 2.2. SAM L10/SAM L11	18
3.	Cortex M4F Family of Devices	26
4.	Cortex M7 Family of Devices 4.1. SAM E70/S70/V70/V71	
5.	MIPS Family of Devices. 5.1. PIC32MZ EF. 5.2. PIC32MZ DA. 5.3. PIC32MK. 5.4. PIC32MX.	40 43 47
6.	Revision History	53
Mic	crochip Information The Microchip Website Product Change Notification Service Customer Support Microchip Devices Code Protection Feature Legal Notice Trademarks Quality Management System Worldwide Sales and Service	54 54 54 54 54 54 55 55 56



1. Cortex M0+ Family of Devices

1.1 SAM D21/SAM D20/SAM D11/SAM D10⁽¹⁾

Note:

1. Most of the collaterals listed below cover the SAM D21 family of devices. They can be extended and easily ported to any of the SAM D20/SAM D11/SAM D10 devices.

Click on the following links to view the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/ On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/ Solutions.

1.1.1 SAM D2x/D1x: Videos

Table 1-1. SAM D2x/D1x: Videos

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining the following: How to Install MPLAB[®] X (IDE) How to Install MPLAB[®] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from MPLAB Harmony v3 repositories on GitHub MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with MPLAB Harmony v3
2	Getting Started with Device/Kit	SAM D21 Xplained Pro Evaluation Kit (ATSAMD21-XPRO)	Explains how to create a simple application on the SAM D21 using MPLAB Harmony v3. The application sends a "Hello World!" string to the PC terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC.	Create Your First Project with SAMD21 using Using MPLAB Harmony v3
3	Getting Started with Device/Kit	SAM D21 Curiosity Nano Evaluation Kit (DM320119)	Explains how to create a simple application on the SAM D21 using MPLAB Harmony v3. The application toggles an LED periodically and prints the LED toggling rate on a serial terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC.	Getting Started with the SAM D21 Curiosity Nano
4	Getting Started with IoT	SAM-IoT WG Board (EV75S95A)	Explains the steps to get started with the SAM-IoT Board and the supported features.	Getting Started with the SAM IoT WG Board
5	IoT	SAM-IoT WG Board (EV75S95A)	Explains the steps to create an IoT-based heart rate monitoring application on the SAM-IoT WG Development Board.	How to Create an IoT Based Heart Rate Monitoring Application
6	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager	MPLAB [®] Code Configurator Content Manager



	continued				
SI. No	Type/ Focus Area	Description		Link	
7 with Software Tools Xplained Pro Evaluation Kit (ATSAMD21-XPRO) or SAM D21 Curiosity Nano Evaluation Kit		covers DM320209 and EV76S68A, the same content can be replicated for SAM D21 Xplained Pro Evaluation Kit (ATSAMD21-XPRO) or SAM D21 Curiosity	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to an MCC- based project.	Getting Started with Harmony v3 Using Code Configurator	
8	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package	
9	Getting started with Solutions	N/A	Introduces the MPLAB Harmony Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package	

1.1.2 SAM D2x/D1x Training Modules

Table 1-2. SAM D2x/D1x Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/Kit	SAM D21 Xplained Pro Evaluation Kit (ATSAMD21- XPRO	Shows how to create an application to get started with the SAM D21 using the MPLAB Harmony v3 software framework. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Peripheral Libraries on SAM D21
2	Getting Started with Device/Kit	The SAM D21 Xplained Pro Evaluation Kit (ATSAMD21- XPRO)	Shows how to create an application to get started with the SAM D21 using the MPLAB Harmony v3 software framework with FreeRTOS. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Drivers on SAM D21 Using FreeRTOS
3	Getting started with tools	N/A	Shows how to create a new MPLAB Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
4	Getting started with tools	N/A	Shows how to open an existing project and use with MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
5	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin, and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content
6	Getting started with tools	Though this training uses the SAM D5x/E5x, the same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using MCC.	Create a new MPLAB Harmony v3 project using MCC
7	Application Specific	SAM D21 Xplained Pro Evaluation Kit (ATSAMD21- XPRO)	Shows how to create a low-power application on the SAM D21 by showcasing the current measurement on Idle and Standby sleep modes. The current consumption data is displayed on the data visualizer.	Low Power Application on SAM D21
8	Migration	Though this training uses the PIC32MZ EF, the same training can be used as a reference for other MCUs.	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC-based Project



•••••	continued			
Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
9	loT	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A) Or SAM D21 Curiosity Nano Evaluation Kit (DM320119)	Shows how to develop an application prototype from a concept without designing a Printed Circuit Board (PCB) using 32-bit MCU-based Curiosity Nano Evaluation Kits and Nano baseboard. This training uses the PIC32CM MC00 Curiosity Nano. The same training can be used for other MCUs that are supported in the Curiosity Nano platform.	Rapid prototyping with 32- bit MCU-based Curiosity Nano

1.1.3 SAM D2x/D1x Virtual/On-Demand Training

Though some of the following virtual trainings are developed using other MCUs, the same training can be easily ported to the SAM D21 MCU.

SI. No	Event	Description	Link
1	Design Week 2022 - Rapid Prototyping	Discusses how to rapidly develop IoT- centered smart appliance control application prototypes from a concept. Refer to items 2, 3, and 4 in the following table for details.	Link
2	Rapid Prototyping with Curiosity Nano: Part I Webinar	Discusses how to rapidly develop an IoT- centered smart appliance control application prototype from a concept. In the first part, The concept of creating a system to capture sensor data and control actuators through an I ² C interface is explained. This demonstration, though it was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit, can be easily ported to the SAM D21 Curiosity Nano Evaluation Kit (DM320119).	Link
3	Rapid Prototyping with Curiosity Nano: Part II Webinar	Discusses how to rapidly develop an IoT- centered smart appliance control application prototype from a concept. In the second part, the concept of creating a system to capture and display sensor data through the UART and SPI interfaces is explained. This demonstration, though it was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit, can be easily ported to the SAM D21 Curiosity Nano Evaluation Kit (DM320119).	Link
4	Rapid Prototyping with Curiosity Nano: Part III Webinar	 Discusses how to rapidly develop an IoT- centered smart appliance control application prototype from a concept. In the third part, the concepts to add more functionality to the project created in the first part of this webinar series is explained: Extending the project to display the data captured by sensors through the SPI. Extending the project to add wireless capability through the UART. This demonstration, though it was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit, can be easily ported to the SAM D21 Curiosity Nano Evaluation Kit (DM320119). 	Link
5	Develop 32-bit MCU Applications Using MPLAB [®] Harmony v3	Discusses the fundamentals of MPLAB Harmony v3, the middleware, and other design tools available for application development. It also showcases a weather station demonstration using the SAM D21 32-bit microcontroller using the SAM D21 Curiosity Nano Evaluation Kit (DM320119).	Link

Table 1-3. SAM D2x/D1x Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- 1. Introduction To MPLAB[®] X IDE
- 2. MPLAB[®] X Tips and Tricks
- 3. Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- 4. MPLAB® Code Configurator (MCC) For Simplified Embedded Software Development
- 5. ARM[®] Cortex[®]-M Architecture Overview
- 6. Getting Started with Writing Code for the Microchip ARM[®] Cortex[®] Microcontrollers
- 7. MPLAB[®] Harmony v3 Fundamentals



- 8. Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- 9. Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- 10. FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications
- 11. Class B Diagnostic Libraries For Functional Safety

1.1.4 SAM D2x/D1x Technical Briefs

Table 1-4. SAM D2x/D1x Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: Explains how to create a simple application on a SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document explains one MCU; however, it can be ported to other MCUs. Note: MPLAB Harmony v3 is configurable through MCC. Refer to items 6 and 7 in SAM D2x/ D1x: Videos for specific instructions to use the MCC.	Link
2	Getting Started	TB3232: Explains how to set up the tools required to get started with MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	Build MPLAB Harmony v3 project with Arm GCC toolchain in MPLAB X IDE.	Link
9	Migration	Application migration from 8-bit PIC18F (MCC) to 32-bit SAM D21 (MHC).	Link
10	Migration	Application migration from 8-bit AVR (MCC) to 32-bit SAM D21 (MHC).	Link
11	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
12	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
13	Peripheral Feature	TB3243: How to Wake-up Fast from an External Event on Cortex M0+ Based MCUs	Link
14	Peripheral Feature	TB3230: Various Timers on SAM Devices	Link
15	Peripheral Feature	TB3222: EEPROM Emulation for Flash-Only Devices	Link
16	MCU Feature	TB3183: What is Sleepwalking? How it helps to reduce the power consumption?	Link
17	Peripheral Feature	TB3170: How the Event System Helps to Lower CPU Load and Power Consumption in Cortex [™] -M0+ Microcontrollers	Link

1.1.5 SAM D2x/D1x Application Notes

Table 1-5. SAM D2x/D1x Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	AN3563: SAM D21 Curiosity Nano: MPLAB Harmony v3 PLIBs Setup and Evaluation	Link
2	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3-based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
3	Feature specific	AN4383: 32-bit Microcontroller Wafer-Level Chip-Scale Package (WLCSP)	Link
4	Migration	PIC18F to PIC24F to SAM D2x Migration and Performance Enhancement Guide	Link
5	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF users	Link



1.1.6 SAM D2x/D1x Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting Started	SAM D21 Curiosity Nano (DM320119)	Getting Started Application on the SAM D21 Curiosity Nano Evaluation Kit	Link
2	Getting Started	SAM D21 Xplained Pro Evaluation Kit (ATSAMD21-XPRO)	Getting Started Application on the SAM D21 Xplained Pro Evaluation Kit	Link
3	loT, Connectivity	SAM D21 Curiosity Nano (DM320119)	Amazon Alexa Connect Kit (ACK) SDK port, Smart Applications and Over the Air (OTA) firmware upgrade on the SAM D21 Curiosity Nano	Link
4	Tracking	SAM D21 Curiosity Nano (DM320119)	Location Tagged SOS Application on the SAM D21 Curiosity Nano and Nano Base for Click boards	Link
5	IoT, Healthcare	SAM D21 Curiosity Nano (DM320119)	Fitness Tracker Application on the SAM D21 Curiosity Nano Evaluation Kit and Nano Base for Click boards	Link
6	loT, Automation	SAM D21 Curiosity Nano (DM320119)	BLE based Weather Station and Motion Sensor Application on the SAM D21 Curiosity Nano and Nano Base for Click boards	Link
7	Low Power	SAM D21 Xplained Pro Evaluation Kit (ATSAMD21-XPRO)	Low-Power Application on the SAM D21 Xplained Pro Evaluation Kit	Link
8	Data Logger	SAM D21 Xplained Pro Evaluation Kit (ATSAMD21-XPRO)	SD Card USB Data Logger Application on the SAM D21 Xplained Pro Evaluation Kit	Link
9	Low Power	SAM D21 Xplained Pro Evaluation Kit (ATSAMD21-XPRO)	AC Sleepwalking Application built with GCC Toolchain on the SAM D21 Xplained Pro Kit	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following links:

- More application demonstrations on SAM D21 Curiosity Nano Evaluation Kit and other Development Boards/Kits having the same part number (ATSAMD21G17D)
- More application demonstrations on SAM D21 Xplained Pro Evaluation Kit and other Development Boards/Kits having the same part number (ATSAMD21J18A)

1.1.7 SAM D2x/D1x Reference Designs/Solutions

Sl. No	Туре	Description	Link
1	Automation, Tracking	Location-Tagged SOS, Asset Tracking or Vehicle Tracking Application: This solution can be used during an emergency to send a distress signal through a location-tagged SOS SMS text message.	Link
2	IoT, Medical	Fitness Tracker Wearables Application: This solution displays heart rate readings measured in beats per minute (bpm) on a low-power E ink display.	Link
3	loT, Automation	Bluetooth [®] Low Energy-Based Weather Station This solution showcases a Bluetooth Low Energy-based solution for environmental or weather monitoring applications. It demonstrates the logging of weather and motion sensor data collected from various sensors to an Android [™] mobile application through Bluetooth Low Energy.	Link
4	Battery Charger	The USB PD Demonstration Board is a USB power delivery battery charger demonstration board featuring the ATSAMD21J18A microcontroller. The battery charger's SEPIC power supply can support the full 20V/5A 100W USB PD specification.	Link
5	Automation	SD [™] Card USB Data Logger Demonstration Application: This solution demonstrates an example of using the MPLAB [®] Harmony v3 File System to access and modify the contents of an SD card using the SDSPI driver, the SPI PLIB, and MPLAB Harmony USB Device Stack to simultaneously enumerate an SD card as a USB Mass Storage Device (MSD).	Link

1.1.8 SAM D2x/D1x Key Links

- SAM D21 Curiosity Nano Evaluation Kit (DM320119)
- SAM-IoT WG Development Board (EV75S95A)



- SAM D21 Xplained Pro Evaluation Kit (ATSAMD21-XPRO)
- MPLAB Harmony Landing Page
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page
- Rapid Prototyping with 32-bit MCUs

1.2 SAM C21/SAM C20/PIC32CM MC/PIC32CM JH ⁽¹⁾

Note:

1. Most of the collaterals listed below are covering the SAM C21 and PIC32CM MC family of devices. They can be easily extended and ported to the SAM C20/PIC32CM JH devices.

Click on the following links to view the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual / On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/ Solutions.

1.2.1 SAM C2x/PIC32CM MC/PIC32CM JH Videos

Table 1-8. SAM C2x/PIC32CM MC/PIC32CM JH Videos

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[®] X (IDE) How to Install MPLAB[®] XC32 Compiler How to install the Configurator How to Download Harmony Framework from MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Device/Kit	SAM C21 Xplained Pro Evaluation Kit (ATSAMC21-XPRO)	Explains how to create a simple application on the SAMC21 using Harmony v3. This application sends a "Hello World!" string to the PC terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC.	Create Your First Project with SAMC21
3	Getting Started with Device/Kit	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	Explains how to create a simple application on the PIC32CM MC00 using Harmony v3. This application toggles an LED toggling periodically and prints the LED toggling rate on a serial terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC.	Getting Started with the PIC32CM MC00 Curiosity Nano
4	loT	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	Explains the implementation of an IoT sensor node on the Google cloud platform. The demonstration is developed on the PIC32CM MC00 Curiosity Nano. Since Google Cloud's IoT Core Service is being discontinued on August 2023, this video will be updated in the future with an alternative cloud service.	Create a Smart Asset Monitor With a PIC32CM MC00 Curiosity Nano Eval Kit and Google Cloud IoT Core



	continued					
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link		
5	Getting Started with S/W Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [*] Code Configurator Content Manager		
6	Getting Started with S/W Tools	The video covers DM320209 and EV76S68A. The video content can be replicated for the SAM C21 Xplained Pro Evaluation Kit (ATSAMC21-XPRO) or the PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A).	Explains how to create a new MPLAB Harmony v3 project using the MCC, and shows how to migrate an MHC-based project to an MCC based project.	Getting Started with Harmony v3 Using Code Configurator		
7	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package		
8	Getting started with Solutions	N/A	Introduces the MPLAB Harmony v3 Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package		

1.2.2 SAM C2x/PIC32CM MC/PIC32CM JH Training Modules

Table 1-9. SAM C2x/PIC32CM MC/PIC32CM	/ JH Training Modules
---------------------------------------	------------------------------

	,	,		
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/Kit	SAM C21N Xplained Pro Evaluation Kit (ATSAMC21N-XPRO)	Shows how to create an application to get started with the SAM C21 using the MPLAB Harmony v3 software framework. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Peripheral Libraries on SAMC2x MCUs
2	Getting Started with Device/Kit	SAM C21 Xplained Pro Evaluation Kit (ATSAMC21- XPRO)	Shows how to create an application to get started with the SAM C21 using the MPLAB Harmony v3 software framework with FreeRTOS. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Drivers on SAM C21 MCUs Using FreeRTOS
3	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) MPLAB Harmony v3 project from scratch.	Create a New MPLAB Harmony v3 Project Using MCC
4	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
5	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content
6	Getting started with tools	This training uses the SAM D5x/E5x device. The same training can be used as a reference for other MCUs.	This tutorial shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a New MPLAB Harmony v3 project Using MCC
7	Migration	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	This tutorial shows how to migrate an application from Advanced Software Framework (ASF) to the MPLAB Harmony v3 software framework using a 32-bit Arm [®] Cortex [®] -based M0+ PIC32CM MC microcontroller.	Migrating ASF SAM C21 Application to MPLAB Harmony v3 PIC32CM MC



•••••	continued				
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link	
8	Application Specific	SAM C21 Xplained Pro Evaluation Kit (ATSAMC21- XPRO)	Shows how to create a low-power application on a SAM D21, showcasing the current measurement on Idle and Standby Sleep modes. The current consumption data is shown on the data visualizer.		
9	Migration	This training uses the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC-based Project	
10	IoT	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	Shows how to develop an application prototype from a concept ,without designing a Printed Circuit Board (PCB) using the 32-bit MCU-based Curiosity Nano Evaluation Kits and Nano baseboard.	Rapid prototyping with 32- bit MCU-based Curiosity Nano	

1.2.3 SAM C2x/PIC32CM MC/PIC32CM JH Virtual/On-Demand Training

SI. No	Event	Description	Link
1	Design Week 2022 - Rapid Prototyping	This session discusses how to rapidly develop loT- centered smart appliance control application prototypes from a concept. Refer to items 2, 3, and 4 in this table for details.	Link
2	Rapid Prototyping with Curiosity Nano: Part I webinar	Discusses how to rapidly develop IoT-centered smart appliance control application prototypes from a concept. In the first part, The concept of creating a system to capture sensor data and control actuators through an I ² C interface is explained. This demonstration, though it was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A), can be easily ported to the SAM D21 Curiosity Nano Evaluation Kit (DM320119).	Link
3	 Rapid Prototyping with Curiosity Nano: Part II webinar Discusses how to rapidly develop IoT-centered smart appliance control application prototypes from a concept. In the second part, the concept of creating a system to capture and display sen data via the UART and SPI interfaces is explained. This demonstration, though it was developed on the PIC32CM MC00 Curiosity Nano Evaluation (EV10N93A), can be easily ported to the SAM D21 Curiosity Nano Evaluation Kit (DM320119). 		Link
4	Rapid Prototyping with Curiosity Nano: Part III webinar	 Discusses how to rapidly develop IoT-centered smart appliance control application prototypes from a concept. In the third part, the concepts to add more functionality to the project created in the first part of this webinar series is explained: Extending the project to display the data captured by sensors through the SPI. Extending the project to add wireless capability through the UART. This demonstration, though it was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A), can be easily ported to the SAM D21 Curiosity Nano Evaluation Kit (DM320119). 	Link
5	Develop 32-bit MCU applications using MPLAB [®] Harmony v3	Discusses the fundamentals of MPLAB Harmony v3, the middleware, and other design tools available for application development. It also showcases a weather station demonstration using the SAM D21 32-bit microcontroller and the SAM D21 Curiosity Nano Evaluation Kit(DM320119). The same demonstration can be ported for PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A).	Link

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- ARM[®] Cortex[®]-M Architecture Overview
- Getting Started with Writing Code for the Microchip ARM[®] Cortex[®] Microcontrollers



- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications
- Introduction to Functional Safety
- Class B Diagnostic Libraries For Functional Safety

1.2.4 SAM C2x/PIC32CM MC/PIC32CM JH Technical Briefs

Table 1-11. SAM C2x/PIC32CM MC/PIC32CM JH Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: This document explains how to create a simple application on a SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. Though this document is explained on one MCU, it can be ported to other MCUs. Note: MPLAB Harmony v3 is configurable through MCC. Refer to items 6 and 7 in SAM C2x/ PIC32CM MC/ PIC32CM JH Videos for specific instructions to use the MCC.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	TB3227: Clock System Configuration and Usage on SAM C2x (Cortex M0+) Devices	Link
9	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
10	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
11	Peripheral Feature	TB3243: How to Wake-up Fast from an External Event on Cortex M0+ Based MCUs	Link
12	Peripheral Feature	TB3230: Various Timers on SAM Devices	Link
13	Peripheral Feature	TB3222: EEPROM Emulation for Flash-Only Devices	Link
14	MCU Feature	TB3183: What is Sleepwalking? How it helps to reduce the power consumption?	Link
15	Peripheral Feature	TB3170: How the Event System Helps to Lower CPU Load and Power Consumption in Cortex [™] -M0+ Microcontrollers	Link

1.2.5 SAM C2x/PIC32CM MC/PIC32CM JH Application Notes

Table 1-12. SAM C2x/PIC32CM MC/PIC32CM JH Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	ADC	AN3589: Using Sigma-Delta Analog-to-Digital Converter (SDADC) on a SAMC MCU	Link
2	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3-based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
3	Feature specific	AN4383: 32-bit Microcontroller Wafer-Level Chip-Scale Package (WLCSP)	Link
4	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF users	Link



1.2.6 SAM C2x/PIC32CM MC/PIC32CM JH Application Demonstrations

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	Getting Started Application Demonstration on the PIC32CM MC00 Curiosity Nano Evaluation Kit using MPLAB Harmony v3.	Link
2	Getting Started	PIC32CM MC00 Curiosity Pro Evaluation Kit (EV15N46A)	Getting Started Application on the PIC32CM MC00 Curiosity Pro Development Board.	Link
3	loT, Automation	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	Smart Appliance Control Application Demonstration on a PIC32CM MC00 Curiosity Nano Evaluation kit.	Link
4	IoT, Automation	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	Temperature-based Fan Speed Control with OLED C click display on a PIC32CM MC00 Curiosity Nano Evaluation kit + Base Board using MPLAB Harmony v3.	Link
5	loT, Automation	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	Smart Tag Google Cloud IoT Core Application on a PIC32CM MC00 Curiosity Nano Evaluation Kit.	Link
6	Getting Started	SAM C21N Xplained Pro Evaluation Kit (ATSAMC21N-XPRO)	Getting Started Application on a SAMC21N Xplained Pro Evaluation Kit.	Link
7	Getting Started	SAM C21N Xplained Pro Evaluation Kit (ATSAMC21N-XPRO)	SDADC Conversion Interrupt Mode Application on a SAMC21N Xplained Pro Evaluation Kit.	Link
8	Getting Started	SAM C21N Xplained Pro Evaluation Kit (ATSAMC21N-XPRO)	SDADC Conversion Polling Mode Application on a SAMC21N Xplained Pro Evaluation Kit.	Link
9	Getting Started	SAM C21 Xplained Pro Evaluation Kit (ATSAMC21-XPRO)	Getting Started with Harmony v3 Drivers on a SAM C21 MCU Using FreeRTOS.	Link
10	Low Power	SAM C21 Xplained Pro Evaluation Kit (ATSAMC21-XPRO)	Low-Power Application on a SAM C21 Xplained Pro Evaluation Kit.	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following links:

- More Application demonstrations on PIC32CM MC00 Curiosity Nano Evaluation Kit and other Development Boards/Kits having the same part number (PIC32CM1216MC00032)
- More application demonstrations on PIC32CM MC00 Curiosity Pro Development Board and other Development Boards/Kits having the same part number (PIC32CM1216MC00048)
- More application demonstrations on SAM C21 Xplained Pro evaluation kit and other Development Boards/Kits having the same part number (ATSAMC21J18A)
- More application demonstrations on SAM C21N Xplained Pro Evaluation Kit and other Development Boards/Kits having the same part number (ATSAMC21N18A)

1.2.7 SAM C2x/PIC32CM MC/PIC32CM JH Reference Designs/Solutions

Table 1-14. SAM C2x/PIC32CM MC/PIC32CM JH Reference Designs/Solutions

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	loT, Automation	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	loT Smart Asset Monitor Demonstration Application	Link
2	IoT, Automation	PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)	IoT Smart Appliance Control Demonstration Application	Link
3	Graphics	SAM C21 Xplained Pro Evaluation Kit (ATSAMC21-XPRO)	Graphical User Interface Demonstrations: MPLAB Harmony v3 has various demonstration examples for creating an intuitive and reliable GUI in applications.	Ref design Link Graphics demo link
4	Wireless Charging	-	Powermat Wireless Charging for Automotive Applications	Link



continued				
Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
5	Motor Control	High-Voltage Development Board (DM330023-3) Low-Voltage Development Board (DM330021-2) PIC32CM MC00 Motor Control Plug-In Module (EV94F66A) SAM C21 Motor Control Plug-In Module (MA320206)	Motor Control for Appliances: Multiple demonstration examples are pre-configured to run on various motor control development boards to make it easy to prototype motor drive applications.	Ref Design Link Motor Control examples

1.2.8 SAM C2x/PIC32CM MC/PIC32CM JH Key Links

- SAM C21N Xplained Pro Evaluation Kit (ATSAMC21N-XPRO)
- SAM C21 Xplained Pro Evaluation Kit (ATSAMC21-XPRO)
- PIC32CM MC00 Curiosity Nano Evaluation Kit (EV10N93A)
- PIC32CM MC00 Curiosity Pro Evaluation Kit (EV15N46A)
- MPLAB Harmony Landing Page.
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page
- Rapid Prototyping with 32-bit MCUs

1.3 SAM L21/SAM L22

Click on the following links to check various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/Solutions.

1.3.1 SAM L2x Videos

Table 1-15. SAM L2x Videos

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[®] X (IDE) How to Install MPLAB[®] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3



continued				
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
2	Getting Started with Device/ Kit	SAM L21 Xplained Pro Evaluation Kit (ATSAML21-XPRO-B) OR SAM L22 Xplained Pro Evaluation Kit (ATSAML22-XPRO-B)	Explains how to create a simple application on the SAMD21 using MPLAB Harmony v3. This application sends a "Hello World!" string to the PC terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions to use the MCC. The same example can be ported to the SAML2x following the same steps.	Create Your First Project with SAMD21
3	Getting Started with Software Tools	N/A	This video explains how to use the MCC Content Manager.	MPLAB [®] Code Configurator Content Manager
4	Getting Started with Software Tools	The video covers DM320209 and EV76S68A. The same content can be replicated for SAM L21 Xplained Pro Evaluation Kit (ATSAML21-XPRO-B).	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to an MCC-based project.	Getting Started with Harmony v3 Using Code Configurator
5	Getting started with Docs	N/A	This video introduces the Quick Docs package to help develop applications on Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package
6	Getting started with Solutions	N/A	This video introduces the MPLAB Harmony v3 Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package

1.3.2 SAM L2x Training Modules

Table 1-16. SAM L2x Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Low Power	SAM L21 Xplained Pro Evaluation Kit (ATSAML21- XPRO-B)	Shows how to create a low-power application on a SAM L21 showcasing the current measurement on different low-power modes. Though the training module is based on the MHC, similar steps and flow can be used to create a project using the MCC.	Low Power Application on SAM L21
2	Getting Started with Device/ Kit	SAM L21 Xplained Pro Evaluation Kit (ATSAML21- XPRO-B)	Shows how to create an application to get started with the SAM D21 using the MPLAB Harmony v3 software framework. This training module content can be easily ported for the SAM L21. Though the training module is based on the MHC, similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Peripheral Libraries on SAM D21
3	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
4	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
5	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content



continued					
	Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
	6	Getting started with tools	While this training is using the SAM D5x/E5x, the same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using MCC.	Create a new MPLAB Harmony v3 project using MCC
	7	Migration	While this training is using the PIC32MZ EF, the same training can be used for other MCUs.	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to an MPLAB Code Configurator (MCC)- based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC-based Project

1.3.3 SAM L2x Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB® Code Configurator (MCC) For Simplified Embedded Software Development
- ARM[®] Cortex[®]-M Architecture Overview
- Getting Started with Writing Code for the Microchip ARM[®] Cortex[®] Microcontrollers
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications
- Class B Diagnostic Libraries For Functional Safety

1.3.4 SAM L2x Technical Briefs

Table 1-17. SAM L2x Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: This document explains how to create a simple application on a SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document is explained on one MCU, it can be ported for other MCUs. Note: MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 in SAM L2x Videos for specific instructions to use the MCC.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
9	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
10	Peripheral Feature	TB3243: How to Wake-up Fast from an External Event on Cortex M0+ Based MCUs	Link



continued				
Sl. No	Type/ Focus Area	Description	Link	
11	Peripheral Feature	TB3230: Various Timers on SAM Devices	Link	
12	Peripheral Feature	TB3222: EEPROM Emulation for Flash-Only Devices	Link	
13	MCU Feature	TB3183: What is Sleepwalking? How it helps to reduce the power consumption?	Link	
14	Peripheral Feature	TB3170: How the Event System Helps to Lower CPU Load and Power Consumption in Cortex [™] -M0+ Microcontrollers	Link	

1.3.5 SAM L2x Application Notes

Table 1-18. SAM L2x Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3-based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Feature specific	AN4383: 32-bit Microcontroller Wafer-Level Chip-Scale Package (WLCSP)	Link
3	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF Users	Link

1.3.6 SAM L2x Application Demonstrations

Table 1-19. SAM L2x Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Demonstration Description	Link
1	Low Power	SAM L21 Xplained Pro Evaluation Kit (ATSAML21-XPRO-B)	Low-Power Application on SAM L21 Xplained Pro Evaluation Kit.	Link
2	IoT	SAM L21 Xplained Pro Evaluation Kit (ATSAML21-XPRO-B)	BLE Fitness Tracker Application on SAM L21 Xplained Pro Evaluation Kit.	Link
3	Automation	SAM L22 Xplained Pro Evaluation Kit (ATSAML22-XPRO-B)	SD Card USB Data Logger Application on SAM L22 Xplained Pro Evaluation Kit using MPLAB Harmony v3.	Link
4	Graphics	SAM L22 Xplained Pro Evaluation Kit (ATSAML22-XPRO-B)	Graphical User Interface Demonstrations: MPLAB Harmony v3 has various demonstration examples for creating an intuitive and reliable GUI in applications.	Reference design Link and Graphics demonstration link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following links:

- More application demonstrations on SAM L21 Xplained Pro Evaluation Kit and other Development Boards/Kits having the same part number (ATSAML21J18B)
- More application demonstrations on SAM L22 Xplained Pro Evaluation Kit and other Development Boards/Kits having the same part number (ATSAML22N18A)

1.3.7 SAM L2x Reference Designs/ Solutions

Table 1-20. SAM L2x Reference Designs/ Solutions

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	loT, Automation	SAM L21 Xplained Pro Evaluation Kit (ATSAML21-XPRO-B)	Bluetooth [®] Low Energy-Based Weather Station Demonstration	Link

1.3.8 SAM L2x Key Links

- SAM L21 Xplained Pro Evaluation Kit (ATSAML21-XPRO-B)
- SAM L22 Xplained Pro Evaluation (ATSAML22-XPRO-B)
- MPLAB Harmony Landing Page



- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page



2. Cortex M23 Family of Devices

2.1 PIC32CM LE00/LS00/LS60

Click on the following links to check various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual / On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/ Solutions.

2.1.1 PIC32CM Lx Videos

Table 2-1. PIC32CM Lx Videos

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[®] X (IDE) How to Install MPLAB[®] XC32 Compiler How to install the Configurator How to Download Harmony Framework from MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Tools	PIC32CM LE00 Curiosity Pro Evaluation Kit (EV80P12A)	Introduces the PIC32CM LE00 Curiosity Pro Evaluation Kit and explains the key features of the board.	PIC32CM LE00 Curiosity Pro Evaluation Kit Overview
3	Getting Started with application	PIC32CM LE00 Curiosity Pro Evaluation Kit (EV80P12A)	Explains how to create a simple application on the PIC32CM LE00 using the MCC. This application demonstrates how to toggle an LED by pressing the switch on a timeout basis and viewing the LED toggling rate on the serial terminal.	Getting Started with PIC32CM LE00 Curiosity Pro Evaluation Kit
4	Getting Started with Device/ Kit	PIC32CM LS60 Curiosity Pro Evaluation Kit (EV76R77A) or PIC32CM LS00 Curiosity Pro Evaluation Kit (EV12U44A)	Introduces TrustZone [®] -based security on the PIC32CM LSx Microcontrollers and shows how to create a simple TrustZone [®] -based application using the MCC. The application has two projects pertaining to Secure and Non-Secure modes of the PIC32CM LS60/LS00 that work together on the same MCU. It offers security isolation between the trusted and the non- trusted resources in the device.	Getting Started With the TrustZone*-based Security on PIC32CM LSx
5	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager	MPLAB [®] Code Configurator Content Manager
6	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package



•••••	continued				
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link	
7	Getting started with Solutions	N/A	Introduces the MPLAB Harmony Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package	

2.1.2 PIC32CM Lx Training Modules

Table 2-2. PIC32CM Lx Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/ Kit	PIC32CM LE00 Curiosity Pro Evaluation Kit (EV80P12A) or PIC32CM LS60 Curiosity Pro Evaluation Kit (EV76R77A) or PIC32CM LS00 Curiosity Pro Evaluation Kit (EV12U44A)	This training module shows how to create an application to get started with the SAM L10 using the MPLAB Harmony v3 software framework. This training module content can be easily ported for the PIC32CM LE00/ LS00/ LS60. Though the training module is based on the MHC, similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Peripheral Libraries on SAM L10
2	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
3	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
4	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin and how to download the MPLAB Harmony v3 framework	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content
5	Getting started with tools	This training uses the SAM D5x/ E5x. The same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC
6	Application Specific	PIC32CM LE00 Curiosity Pro Evaluation Kit (EV80P12A) or PIC32CM LS60 Curiosity Pro Evaluation Kit (EV76R77A) or PIC32CM LS00 Curiosity Pro Evaluation Kit (EV12U44A)	Shows how to create a low-power application on a SAM L1x, showcasing the current measurement on Idle and Standby Sleep modes. The current consumption data is shown on the data visualizer. The same training module methodology can be ported to the PIC32CM Lx MCU.	Low Power Application on SAM L10
7	Product Feature	PIC32CM LE00 Curiosity Pro Evaluation Kit (EV80P12A) or PIC32CM LS60 Curiosity Pro Evaluation Kit(EV76R77A) or PIC32CM LS00 Curiosity Pro Evaluation Kit (EV12U44A)	Shows how to create an Arm [®] TrustZone [®] feature application on the SAM L11 microcontroller (MCU) using the MPLAB Harmony v3 software framework.	Arm [®] TrustZone [®] Getting Started Application on SAM L11 MCUs

2.1.3 PIC32CM Lx Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

Introduction To MPLAB[®] X IDE



- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- ARM[®] Cortex[®]-M Architecture Overview
- Getting Started with Writing Code for the Microchip ARM[®] Cortex[®] Microcontrollers
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications

2.1.4 PIC32CM Lx Technical Briefs

Table 2-3. PIC32CM Lx Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: This document explains how to create a simple application on SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. Though this document is explained on one MCU, it can be ported for other MCUs. Note: MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 in PIC32CM Lx Videos for specific instructions to use the MCC.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
9	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
10	Peripheral Feature	TB3306: Dual Developer Application Development Use Case with TrustZone on SAM L11 Using MPLAB Harmony v3	Link
11	Low Power	TB3318: Peripheral Power Consumption in Standby Mode for SAM L10/L11 Family of Devices	Link
12	Peripheral Feature	TB3222: EEPROM Emulation for Flash-Only Devices	Link
13	MCU Feature	TB3183: What is Sleepwalking? How it Helps to Reduce Power Consumption?	Link

2.1.5 PIC32CM Lx Application Notes

Table 2-4. PIC32CM Lx Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	AN4511: Getting Started with the PIC32CM LE00/LS00/LS60 Curiosity Pro Board	Link
2	loT, Connectivity	AN4152 - PIC32CM LS00/LS60 Ultra Low-Power Secure LoRa Demonstration	Link
3	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
4	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF Users	Link



2.1.6 PIC32CM Lx Application Demonstrations

 Table 2-5. PIC32CM Lx Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting started	PIC32CM LE00 Curiosity Pro	Getting Started Extended Application on PIC32CM LE00 Curiosity Pro Evaluation Kit	Link
2	Getting started feature	PIC32CM LS00 Curiosity Pro	TrustZone Getting Started on PIC32CM LS00 Curiosity Pro Evaluation Kit	Link
3	Getting started feature	PIC32CM LS60 Curiosity Pro	TrustZone Getting Started on PIC32CM LS60 Curiosity Pro Evaluation Kit	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following links:

- More application demonstrations on PIC32CM LS60 Curiosity Pro Evaluation Kit and other Development Boards/Kits having the same part number (PIC32CM5164LS60100)
- More application demonstrations on PIC32CM LS00 Curiosity Pro Evaluation Kit and other Development Boards/Kits having the same part number (PIC32CM5164LS00100)
- More application demonstrations on PIC32CM LE00 Curiosity Pro Evaluation Kit and other Development Boards/Kits having the same part number (PIC32CM5164LE00100)

2.1.7 PIC32CM Lx Reference Designs/ Solutions

Table 2-6. PIC32CM Lx Reference Designs/ Solutions

SI. No	Туре	Hardware Board/ Kit Used	Description	Link
1	PTC, MCU feature	PIC32CM LE00 ULP Water-Tolerant Touch Reference Design (EV55S83A)	Water Tolerant Demonstration Application	Link

2.1.8 PIC32CM Lx Key Links

- PIC32CM LS60 Curiosity Pro Evaluation Kit (EV76R77A)
- PIC32CM LS00 Curiosity Pro Evaluation Kit (EV12U44A)
- PIC32CM LE00 Curiosity Pro Evaluation Kit (EV80P12A)
- PIC32CM LE00 ULP Water-Tolerant Touch Reference Design (EV55S83A)
- MPLAB Harmony Landing Page.
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page

2.2 SAM L10/SAM L11

Click on the below links to check various collaterals.

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.



2.2.1 SAM L1x Videos

Table 2-7. SAM L1x Videos

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[®] X (IDE) How to Install MPLAB[®] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Device/ Kit	SAM L11 Xplained Pro Evaluation Kit (DM320205) or SAM L10 Xplained Pro Evaluation Kit (DM320204)	Explains how to create a simple application on the SAM L11 using Harmony v3. This application sends a "Hello World!" string to the PC terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions to use the MCC.	Create Your First Project with SAML11
3	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [®] Code Configurator Content Manager
4	Getting Started with Software Tools	The video covers DM320209 and EV76S68A. The same content can be replicated for SAM L10/L11 Xplained Pro Evaluation Kits (DM320205/DM320204).	This video explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to an MCC-based project.	Getting Started with Harmony v3 Using Code Configurator
5	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package
6	Getting started with Solutions	N/A	Introduces the MPLAB Harmony Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package

2.2.2 SAM L1x Training Modules

Table 2-8. SAM L1x Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/Kit	SAM L11 Xplained Pro Evaluation Kit (DM320205) or SAM L10 Xplained Pro Evaluation Kit (DM320204)	Shows how to create an application to get started with the SAM L10 using the MPLAB Harmony v3 software framework. This training module content can be easily ported for the PIC32CM LE00/ LS00/ LS60.	Getting Started with Harmony v3 Peripheral Libraries on SAM L10
2	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony project from scratch.	Create a new MPLAB Harmony v3 project using MCC
3	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project



	continued				
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link	
4	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content	
5	Getting started with tools	This training uses the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC	
6	Application Specific	SAM L11 Xplained Pro Evaluation Kit (DM320205) or SAM L10 Xplained Pro Evaluation Kit (DM320204)	Shows how to create a low-power application on a SAM L1x showcasing the current measurement on Idle and Standby Sleep modes. The current consumption data is shown on the data visualizer. The same training module methodology can be ported to the SAM L1x MCU.	Low Power Application on SAM L10	
7	Product Feature	SAM L11 Xplained Pro Evaluation Kit (DM320205)	Shows how to create an Arm [®] TrustZone [®] feature application on the SAM L11 microcontroller (MCU) using the MPLAB Harmony v3 software framework.	Arm [®] TrustZone [®] Getting Started Application on SAM L11 MCUs	

2.2.3 SAML1x Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- ARM[®] Cortex[®]-M Architecture Overview
- Getting Started with Writing Code for the Microchip ARM® Cortex® Microcontrollers
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications

2.2.4 SAM L1x Technical Briefs

Table 2-9. SAM L1x Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: This document explains how to create a simple application on a SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. Though this document is explained on one MCU, it can be ported for other MCUs. Note: MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 in SAM L1x Videos for specific instructions to use the MCC.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link



	continued		
Sl. No	Type/ Focus Area	Description	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
9	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
10	Peripheral Feature	TB3306: Dual Developer Application Development Use Case with TrustZone on SAM L11 Using MPLAB Harmony v3	Link
11	Low Power	TB3318: Peripheral Power Consumption in Standby Mode for SAM L10/L11 Family of Devices	Link
12	Peripheral Feature	TB3222: EEPROM Emulation for Flash-Only Devices	Link
13	MCU Feature	TB3183: What is Sleepwalking? How it Helps to Reduce the Power Consumption?	Link

2.2.5 SAM L1x Application Notes

Table 2-10. SAM L1x Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: <i>MPLAB Harmony v3 Project Migration</i> application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Feature specific	AN4383: 32-bit Microcontroller Wafer-Level Chip-Scale Package (WLCSP).	Link
3	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF Users.	Link
4	Op Amp, ADC	AN2794: SAM L10/L11: OPAMP as ADC Gain Amplifier. This document introduces the configuration and usage of the op amp module, different built-in modes, and presents an application example. In the application example, one of the operational amplifiers is configured as a non-inverting gain amplifier with the output internally connected to the ADC. With this setup, the op amp operates as a gain amplifier stage for ADC sampling.	Link
5	MCU Feature	AN2775: CPU Usage Demonstration Using DMAC for SAM L10/L11: This document demonstrates the CPU usage when an application is executed with or without the DMA.	Link
6	Bootloader	AN2699: UART Bootloader SAM L10 and L11: This document describes the design and operation of a UART Bootloader for the SAM L10 and SAM L11 devices.	Link
7	IOT, Security	AN2835: SAML11 Ultra Low-Power Secure LoRa Application Note.	Link
8	Bootloader, Security	AN2698: Secure Bootloader SAML11.	Link

2.2.6 SAM L1x Application Demonstrations

Table 2-11. SAM L1x Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting Started	SAM L10 Xplained Pro Evaluation Kit (DM320204)	Getting Started Application on SAM L10 Xplained Pro Evaluation Kit	Link
2	Security	SAM L11 Xplained Pro Evaluation Kit (DM320205)	TrustZone Getting Started Application on the SAM L11 Xplained Pro Evaluation Kit	Link
3	Low Power	SAM L10 Xplained Pro Evaluation Kit (DM320204)	Low-Power Application on the SAM L10 Xplained Pro Evaluation Kit	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following links:

- More application demonstrations on SAM L10 Xplained Pro Evaluation Kit and other Development Boards/Kits having the same part number (ATSAML10E16A)
- More application demonstrations on SAM L11 Xplained Pro Evaluation Kit and other Development Boards/Kits having the same part number (ATSAML11E16A)



2.2.7 SAM L1x Key Links

- SAML11 Xplained Pro Evaluation kit (DM320205)
- SAM L10 Xplained Pro Evaluation kit (DM320204)
- MPLAB Harmony Landing Page
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page



3. Cortex M4F Family of Devices

3.1 SAM D5x/E5x

Click on the following links to check various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/ Solutions.

3.1.1 SAM D5x/E5x Videos

Table 3-1. SAM D5x/E5x Videos

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[*] X (IDE) How to Install MPLAB[*] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Device/Kit	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Explains how to create a simple application for the SAME54 using MPLAB Harmony v3. This application sends a "Hello World!" string to the PC terminal. Microchip is moving from the MHC to the MCC. Refer to items 6 and 7 in the table.	Create Your First Project with SAME54
3	Getting Started with Device/Kit	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Explains how to create a simple application for the SAME51 using MPLAB Harmony v3. This application toggles an LED periodically and prints the LED toggling rate on a serial terminal. Microchip is moving from the MHC to the MCC. Refer to items 6 and 7 in the table.	Getting Started with SAM E51 Curiosity Nano
4	loT	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Explains the steps to Create an IoT-Based Heart Rate Monitoring Application. The application displays heart rate readings (in beats per minute (bpm)) on a very low-power consuming display and posts this Heart Rate data to the Microchip Bluetooth Data (MBD) Android mobile application through Bluetooth Low Energy.	How to Create a BLE Fitness Tracker Application on SAM E51 Curiosity Nano
5	Getting Started with Device/ Kit	SAM E54 Curiosity Ultra Development Board (DM320210)	Explains how to create a simple application for the SAME51 using MPLAB Harmony v3. This application toggles an LED periodically and prints the LED toggling rate on a serial terminal. The demonstration application has additional functionality to print the current room temperature using an on board temperature sensor.	Getting Started with the SAM E54 Curiosity Ultra



	continued				
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link	
6	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [*] Code Configurator Content Manager	
7	Getting Started with Software Tools	Video covers Curiosity PIC32MZ Ef 2.0 Development Board (DM320209) and SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to an MCC based project.	Getting Started with Harmony v3 Using Code Configurator	
8	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package	
9	Getting started with Solutions	N/A	Introduces the MPLAB Harmony v3 Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package	

3.1.2 SAM D5x/E5x Training Modules

Table 3-2. SAM D5x/E5x Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/ Kit	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Shows how to create an application to get started with the SAM D5x/ E5x using the MPLAB Harmony v3 software framework. This training module is based on the MHC. The same flow can be used to create a project for the MCC.	Getting Started with Harmony v3 Peripheral Libraries on SAM D5x/E5x
2	Getting Started with Device/ Kit	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Shows how to create an application to get started with the SAME5x using the MPLAB Harmony v3 software framework with FreeRTOS. This training module is based on the MHC. The same flow can be used to create a project for the MCC.	Getting Started with Harmony v3 Drivers on SAM E54 MCUs Using FreeRTOS
3	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
4	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
5	Getting started with tools	N/A	Shows how to install the MPLAB [*] Code Configurator (MCC) plugin and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content
6	Getting started with tools	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC
7	Application Specific	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Shows how to create a low-power application on a SAM E54 showcasing the current measurement on Idle and Standby Sleep modes. The current consumption data is shown on a data visualizer.	Low Power Application on SAM E54
8	Migration	Though this training is using PIC32MZ EF, the same training can be used for other MCUs	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC-based Project



	continued				
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link	
9	AI/ ML	Integrated Graphics and Touch (IGaT) Curiosity Evaluation Kit (EV14C17A)	Shows how to create an Artificial Intelligence/Machine Learning (Al/ML) application using TensorFlow Lite for Microcontrollers (TFLM) to recognize handwritten digits on a SAM E51 Integrated Graphics and Touch (IGAT) Curiosity Evaluation Kit.	Digit Recognition AI/ML Application on SAM E51 IGAT	
10	Motor control	dsPICDEM MCLV-2 Development Board Low Voltage (DM330021-2) and ATSAME54 Motor Control Plugin Module (MA320207)	Shows how to create a motor control application Brushless DC (BLDC) block commutation using a hall sensor on a SAM E54 microcontroller. This training module is based on the MHC. The same flow can be used to create a project for the MCC.	Create your first Motor Control Application	
11	loT	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Shows how to develop an application prototype from a concept without designing a Printed Circuit Board (PCB) using the 32-bit MCU-based Curiosity Nano Evaluation Kits and Nano baseboard. This training uses the PIC32CM MC00 Curiosity Nano. The same training can be used for other MCUs that are supported on the Curiosity Nano platform.	Rapid prototyping with 32-bit MCU-based Curiosity Nano	

3.1.3 SAM D5x/E5x Virtual/On-Demand Training

Some of the following virtual trainings were developed using other MCUs. The same trainings can be ported to the SAM E51 Curiosity Nano Evaluation Kit.

Table 3-3. SAM D5x/E5x Virtual/On-Demand	Training
--	----------

Sl. No	Event	Description	Link
1	Design Week 2022 - Rapid Prototyping Connected Applications With 32-bit Microcontrollers	Discusses how to rapidly develop an IoT-centered smart appliance control application prototype from a concept. Refer to items 2, 3, and 4 in this table for details.	Link
2	Rapid Prototyping with Curiosity Nano: Part I webinar	Discusses how to rapidly develop an IoT-centered smart appliance control application prototype from a concept. In the first part, The concept of creating a system to capture sensor data and control actuators through an I ² C interface is explained. This demonstration was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit. It can be easily ported to the SAM E51 Curiosity Nano Evaluation Kit (EV76S68A).	Link
3	Rapid Prototyping with Curiosity Nano: Part II webinar	Discusses how to rapidly develop an IoT-centered smart appliance control application prototype from a concept. In the second part, the concept of creating a system to capture and display sensor data through the UART and SPI interfaces is explained. This demonstration was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit. It can be easily ported to the SAM E51 Curiosity Nano Evaluation Kit (EV76S68A).	Link
4	Rapid Prototyping with Curiosity Nano: Part III webinar	 Discusses how to rapidly develop an IoT-centered smart appliance control application prototype from a concept. In the third part, the concepts needed to add more functionality to the project created in the first part of this webinar series is explained: Extending the project to display the data captured by sensors through the SPI. Extending the project to add wireless capability through the UART. This demonstration was developed on the PIC32CM MC00 Curiosity Nano Evaluation Kit. It can be easily ported to the SAM E51 Curiosity Nano Evaluation Kit (EV76S68A). 	Link
5	Develop 32-bit MCU applications using MPLAB [®] Harmony v3	Discusses the fundamentals of MPLAB Harmony v3, the middleware, and other design tools available for application development. It showcases a weather station demonstration using the SAM D21 32-bit microcontroller using the SAM D21 Curiosity Nano (DM320119). The same can be ported for the SAM E51 Curiosity Nano Evaluation Kit (EV76S68A).	Link

More virtual trainings are available at Microchip University. Click on the following links for more details:



- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB® Code Configurator (MCC) For Simplified Embedded Software Development
- ARM[®] Cortex[®]-M Architecture Overview
- Getting Started with Writing Code for the Microchip ARM[®] Cortex[®] Microcontrollers
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications
- Introduction to Functional Safety
- Class B Diagnostic Libraries For Functional Safety
- Get Started Simplifying Your IoT Design with Azure RTOS
- Build and manage an IoT device with the Microsoft Azure IoT service and the Microchip SAME54 Xplained Pro evaluation kit

3.1.4 SAM D5x/E5x Technical Briefs

Table 3-4. SAM D5x/E5x Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: This document explains how to create a simple application on a SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document is explained on one MCU, it can be ported for other MCUs. Note: Microchip is moving from the MHC to the MCC. Refer to items 6 and 7 in the Videos table.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	TB3226: Clock System Configuration and Usage on SAM E5x (Cortex M4) Devices	Link
9	Migration	TB3298: How to Move an Application into a Desired Flash Memory Location with the Help of Linker Script on SAM E54	Link
10	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
11	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
12	Peripheral Feature	TB3230: Various Timers on SAM Devices	Link
13	Peripheral Feature	TB3222: EEPROM Emulation for Flash-Only Devices	Link
14	MCU Feature	TB3183: What is Sleepwalking? How it helps to reduce the power consumption?	Link



3.1.5 SAM D5x/E5x Application Notes

Table 3-5. SAM D5x/E5x Application Notes

Sl. No	Type/ Focus Area	Description	Note Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	TCP/IP	AN4833: File Transfer Protocol Using MPLAB Harmony v3 TCP/IP Stack for SAM E54 MCU	Link
3	Security	AN3923: AES Cipher Modes Using MPLAB Harmony v3 for the SAM E54	Link
4	Bootloader	AN3767: Live Update Application on SAM E54 MCU Using MPLAB Harmony v3	Link
5	Bootloader	AN3508: Dual Bank Bootloader on SAM E54 Microcontroller (MCU) Using MPLAB Harmony v3	Link
6	Low Power	AN3342: SleepWalking with Event System Using the SAM E54	Link
7	Feature specific	AN4383: 32-bit Microcontroller Wafer-Level Chip-Scale Package (WLCSP)	Link
8	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF Users	Link

3.1.6 SAM D5x/E5x Application Demonstrations

Table 3-6. SAM D5x/E5x Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting started	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Getting Started Application on the SAM E51 Curiosity Nano Evaluation Kit.	Link
2	Getting started	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Getting Started Application on the SAM E54 Xplained Pro Evaluation Kit.	Link
3	Getting started	SAM E54 Curiosity Ultra Development Board (DM320210)	Getting Started Application with the SAM E54 Curiosity Ultra Development Board.	Link
4	ют	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	BLE Fitness Tracker Application on the SAM E51 Curiosity Nano Evaluation Kit and Nano Base for Click boards.	Link
5	IoT	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Google Cloud IoT Core Application on the SAM E51 Curiosity Nano Evaluation Kit.	Link
6	Low Power	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Low-Power Application Demonstration on the SAM E51 Curiosity Nano Evaluation Kit with OLED C.	Link
7	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Weather Click Example	Link
8	HMI	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Eink Display Bundle Click example	Link
9	IoT, Medical	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Heart Rate 9 Click Example	Link
10	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	IR Thermo 2 Click Example	Link
11	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	10DOF Click Example	Link
12	Display	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	LED Driver 3 Click Example	Link
13	Storage	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	EEPROM 4 Click Example	Link
14	Gaming	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Thumbstick Click Example	Link
15	Click Extension	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	XPRO Adapter Click Example	Link
16	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Fan Click Example	Link
17	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	GSM GPS Click Example	Link
18	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	PIR Click Example	Link
19	Connectivity	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	USB UART Click Example	Link
20	Display	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	OLED C Click Example	Link
21	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	WIFI 7 Click Example	Link
22	IoT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	RFID Click Example	Link
23	Connectivity	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	USB I2C Click Example	Link



continued						
Sl. No	Туре	Hardware Board/ Kit Used	Description	Link		
24	loT, Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	BLE 2 Click Example	Link		
25	Automation	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	GRID EYE Click Example	Link		
26	Wireless Connectivity	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	LR Click Example	Link		
27	Connectivity	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	USB SPI Click Example	Link		
28	Automotive	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	CAN to USB bridge Application using SAM E54 Xplained Pro Evaluation Kit.	Link		
29	Consumer	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Vending Machine Application Demonstration on the SAM E54 Xplained Pro Evaluation Kit using MP.	Link		
30	Low Power	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Low-Power Application on the SAM E54 Xplained Pro Evaluation Kit.	Link		
31	Low Power	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	SleepWalking Application on the SAM E54 Xplained Pro Evaluation Kit.	Link		
32	Automation	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	EEPROM Temperature Logger Application on the SAM E54 Xplained Pro Evaluation Kit using FreeRTOS.	Link		
33	Automation	SAM E54 Curiosity Ultra Development Board (DM320210)	Motion Surveillance Application on the SAM E54 Curiosity Ultra Development Board.	Link		
34	Bootloader	SAM E54 Curiosity Ultra Development Board (DM320210)	Live Update Application on the SAM E54 Curiosity Ultra Development Board.	Link		
35	Audio, Consumer	SAM E54 Curiosity Ultra Development Board (DM320210)	SD Card USB Audio Player on the SAM E54 Curiosity Ultra Development Board + maXTouch [®] Curiosity Pro Board using Legato Graphics.	Link		

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following links:

- More application demonstrations on SAM E51 Curiosity Nano Evaluation Kit and other Development Boards/Kits having the same part number (ATSAME51J20A)
- More application demonstrations on SAM E54 Xplained Pro Evaluation Kit and other Development Boards/Kits having the same part number (ATSAME54P20A)
- More application demonstrations on SAM E54 Curiosity Ultra Development Board and other Development Boards/Kits having the same part number (ATSAME54P20A)
- More application demonstrations on IGAT Kit and other Development Boards/Kits having the same part number (ATSAME51J20A)

3.1.7 SAM D5x/E5x Reference Designs/Solutions

Table 3-7. SAM D5x/E5x Reference Designs/ Solutions

SI. No	Туре	Hardware Board/ Kit Used	Description	Link
1	НМІ	Integrated Graphics and Touch (IGaT) Curiosity Evaluation Kit (EV14C17A)	Low-Cost GUI With Graphics and Touchscreen Demonstration.	Link
2	НМІ	Integrated Graphics and Touch (IGaT) Curiosity Evaluation Kit (EV14C17A) or SAM E54 Curiosity Ultra Development Board (DM320210)	Graphical User Interface Demonstrations: MPLAB Harmony v3 has various demonstration examples for creating an intuitive and reliable GUI in applications.	Ref design Link and Graphics demonstration link



	continued						
SI. No	Туре	Hardware Board/ Kit Used	Description	Link			
3	Motor Control	dsPICDEM MCLV-3 Development Board High Voltage (DM330023-3) dsPICDEM MCLV-2 Development Board Low Voltage (DM330021-2) and ATSAME54 Motor Control Plugin Module (MA320207)	Motor Control for Appliances: There are multiple demonstration examples, which are pre-configured to run on Microchip's various motor control development boards for easy prototyping of motor drive applications.	Ref Design Link and Motor Control examples			
4	Connectivity	SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)	Vending Machine Demonstration: This solution demonstrates an embedded network application to update and track the status of the drinks being offered in a vending machine.	Link			
5	loT	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	IoT Smart Appliance Control Demonstration: This solution showcases smart control of a fan through an Android [™] - based smartphone using a Bluetooth [®] Low Energy (BLE) connection. This solution is done for the PIC32CM MC00 Curiosity Nano. It can be ported for the SAM E51 Curiosity Nano (EV76S68A).	Link			
6	IoT	SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)	Fitness Tracker Wearables Demonstration: This fitness tracker demonstration displays the heart rate readings measured in beats per minute (bpm) on a low-power E ink display, and optionally posts this data to the Microchip Bluetooth [®] Data mobile application for Android [™] through Bluetooth Low-Energy technology.	Link			

3.1.8 SAM D5x/E5x Key Links

- SAM E51 Curiosity Nano Evaluation Kit (EV76S68A)
- SAM E54 Xplained Pro Evaluation Kit (ATSAME54-XPRO)
- Integrated Graphics and Touch (IGaT) (EV14C17A)
- SAM E54 Curiosity Ultra Development Board (DM320210)
- MPLAB Harmony Landing Page.
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page
- 32-bit MCUs Rapid Prototyping page

3.2 SAM G5x

Click on the following links to check the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/Solutions.



3.2.1 SAM G5x Videos

Table 3-8. SAM G5x Videos

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[*] X (IDE) How to Install MPLAB[*] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions for using the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Device/ Kit	SAM G55 Xplained Pro Evaluation kit (ATSAMG55-XPRO)	Explains how to create a simple application on the SAME54 using MPLAB Harmony v3. This application sends a "Hello World!" string to the PC terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions for using the MCC. The same example can be ported to the SAM G55 Xplained Pro Evaluation Kit (ATSAMG55-XPRO) following the same steps.	Create Your First Project with SAME54
3	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [*] Code Configurator Content Manager
4	Getting Started with Software Tools	The video covers DM320209 and EV76S68A. The same content can be replicated for the SAM G55 Xplained Pro Evaluation kit (ATSAMG55-XPRO).	Explains how to create a new MPLAB Harmony v3 project using the MCC, and shows how to migrate an MHC-based project to an MCC-based project.	Getting Started with Harmony v3 Using Code Configurator
5	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products with the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package
6	Getting started with Solutions	N/A	Introduces the MPLAB Harmony v3 Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package

3.2.2 SAM G5x Training Modules

Table 3-9. SAM G5x Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/Kit	SAM G55 Xplained Pro Evaluation kit (ATSAMG55- XPRO)	Shows how to create an application to get started with the SAM D5x/ E5x using the MPLAB Harmony v3 software framework. The training module is based on the MHC, similar steps and flow can be used to create a project using the MCC. The same example can be ported to the SAM G5x following the same steps.	Getting Started with Harmony v3 Peripheral Libraries on SAM D5x/E5x
2	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
3	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project



•••••	continued						
Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link			
4	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content			
5	Getting started with tools	This training uses the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC			
6	Migration	This training uses the PIC32MZ EF. The same training can be used for other MCUs.	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC- based Project			

3.2.3 SAM G5x Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- ARM[®] Cortex[®]-M Architecture Overview
- Getting Started with Writing Code for the Microchip ARM[®] Cortex[®] Microcontrollers
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications

3.2.4 SAM G5x Technical Briefs

Table 3-10. SAM G5x Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: This document explains how to create a simple application on a SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. Though this document is explained on one MCU, it can be ported to other MCUs. Note: Microchip is moving from the MHC to the MCC. Refer to items 3 and 4 in the Videos table.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
9	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
10	Peripheral Feature	TB3230: Various Timers on SAM Devices	Link



	continued				
Sl. No	Type/ Focus Area	Description	Link		
11	Peripheral Feature	TB3222: EEPROM Emulation for Flash-Only Devices	Link		
12	MCU Feature	TB3183: What is Sleepwalking? How it helps to reduce the power consumption?	Link		
13	Peripheral	TB3181: What is TWI? How to configure the TWI for I ² C Communication	Link		

3.2.5 SAM G5x Application Notes

Table 3-11. SAM G5x Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Feature specific	AN4383: 32-bit Microcontroller Wafer-Level Chip-Scale Package (WLCSP)	Link
3	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF Users	Link

3.2.6 SAM G5x Application Demonstrations

More application demonstrations are available at Microchip's MPLAB Harmony v3 GitHub repositories. Refer to the following link:

• Examples for SAMG55

3.2.7 SAM G5x Reference Designs/Solutions

Table 3-12. SAM G5x Reference Designs/Solutions

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Audio	SAM G55 Audio Curiosity Development Board (EV78Y10A)	SAM G55 Audio Curiosity Development Board	Link

3.2.8 SAM G5x Key Links

- SAM G55 Xplained Pro Evaluation Kit (ATSAMG55-XPRO)
- MPLAB Harmony Landing Page
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page



4. Cortex M7 Family of Devices

4.1 SAM E70/S70/V70/V71

Click on the following links to check the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/Solutions.

4.1.1 SAM E70/S70/V70/V71 Videos

Table 4-1. SAM E70/S70/V70/V71 Videos

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[®] X (IDE) How to Install MPLAB[®] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Device/ Kit	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	Explains how to create a simple application on the SAME70 using MPLAB Harmony v3. This application sends a "Hello World!" string to the PC terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 6 and 7 for specific instructions to use the MCC.	Create Your First Project with SAM E70
3	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [*] Code Configurator Content Manager
4	Getting Started with Software Tools	The video covers DM320209 and EV76S68A. The same content can be replicated for the SAM E70/SAM V71 Evaluation Kits.	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to an MCC based project.	Getting Started with Harmony v3 Using Code Configurator
5	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package
6	Getting started with Solutions	N/A	Introduces the MPLAB Harmony v3 Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package



4.1.2 SAM E70/S70/V70/V71 Training Modules

Table 4-2. SAM E70/S70/V70/V71 T	raining Modules
----------------------------------	-----------------

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/Kit	SAM E70 Xplained Ultra Evaluation Kit (DM320113) or SAM V71 Xplained Ultra Evaluation Kit (ATSAMV71- XULT)	Shows how to create an application to get started with the SAM E70/S70/V70/V71 using the MPLAB Harmony v3 software framework. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Peripheral Libraries on SAM E70/S70/V70/V71 MCUs
2	Getting Started with Device/Kit	SAM E70 Xplained Ultra Evaluation Kit (DM320113) or SAM V71 Xplained Ultra Evaluation Kit (ATSAMV71- XULT)	Shows how to create an application to get started with Drivers and System Services on the SAM E70/S70/V70/V71 using the MPLAB Harmony v3 software framework. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Drivers and System Services on SAM E70/S70/V70/V71 MCUs
3	Getting Started with Device/Kit	SAM E70 Xplained Ultra Evaluation Kit (DM320113) or SAM V71 Xplained Ultra Evaluation Kit (ATSAMV71- XULT)	Shows how to create an application to get started with the SAM E70/S70/V70/V71 using the MPLAB Harmony v3 software framework with FreeRTOS. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Drivers on SAM E70/S70/V70/V71 MCUs using FreeRTOS
4	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
5	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
6	Getting started with tools	N/A	Shows how to install the MPLAB [*] Code Configurator (MCC) plugin, and how to download MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content
7	Getting started with tools	This training uses the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC
8	Migration	This training uses the PIC32MZ EF. The same training can be used for other MCUs.	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC- based Project
9	USB	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	Shows how to create a simple USB CDC class serial terminal menu application and will help with getting started on developing a USB-based application for SAM MCUs using the MPLAB Harmony v3 software framework.	Getting Started with USB on SAM MCUs Using MPLAB [®] Harmony v3

4.1.3 SAM E70/S70/V70/V71 On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- ARM[®] Cortex[®]-M Architecture Overview
- Getting Started with Writing Code for the Microchip ARM[®] Cortex[®] Microcontrollers



- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications
- Introduction to Functional Safety
- Class B Diagnostic Libraries For Functional Safety

4.1.4 SAM E70/S70/V70/V71 Technical Briefs

Table 4-3. SAM E70/S70/V70/V71 Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3231: This document explains how to create a simple application on a SAM MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document is explained on one MCU. However, it can be ported for other MCUs. Note: Microchip is moving from the MHC to the MCC. Refer to items 6 and 7 in the Videos table.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link
9	Getting Started	TB3246: How to Use the MPLAB Harmony v3 Debug System Service	Link
10	Peripheral	TB3181: What is TWI? How to configure the TWI for I ² C Communication	Link
11	Peripheral Feature	TB3222: External Memory on SAM E70/S70/V70/V71 MCUs	Link
12	MCU Feature	TB3195: Managing Cache Coherency on CortexM7 Based SAM Devices	Link
13	MCU Feature	TB3260: How to Create Non-Cacheable Memory Region on CortexM7 (SAM S70/ E70/ V70/ V71) MCUs Using MPLAB Harmony v3	Link
14	MCU Feature	TB3295: Handling Cache Coherency Issues at Runtime Using Cache Maintenance Operations on Cortex-M7 MCUs Using MPLAB Harmony v3	Link
15	MCU Feature	TB3240: How to Use the TCM on A Cortex-M7 Based MCU with the XC32 Compiler	Link
16	MCU Feature	TB3182: How to use Differential ADC on SAM V7x/E7x/S7x MCUs	Link

4.1.5 SAM E70/S70/V70/V71 Application Notes

Table 4-4. SAM E70/S70/V70/V71 Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Migration	AN3346: Introduction to MPLAB and Harmony v3 for Atmel Studio and ASF Users	Link
3	Peripheral Feature	AN4686: Watchdog Timer (WDT) on ATSAM E70/S70/V70/V71 Devices Using MPLAB Harmony v3	Link
4	Peripheral Feature	AN3443: Execute-In-Place (XIP) with QSPI on Cortex-M7 MCUs Using MPLAB Harmony v3	Link
5	Peripheral Feature	AN3466: Using XDMAC with QSPI on Arm Cortex-M7 MCUs Using MPLAB Harmony v3	Link
6	TCP/ IP	AN3475: File Transfer Protocol Using MPLAB Harmony v3 TCP/IP Stack	Link



4.1.6 SAM E70/S70/V70/V71 Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting started	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	Getting Started Application on the SAM E70 Xplained Ultra Evaluation Kit.	Link
2	Getting started	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	Getting Started Application using MPLAB Harmony v3 Drivers on a SAM E70 Xplained Ultra Evaluation Kit.	Link
3	Getting started	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	Getting Started Application using MPLAB Harmony v3 Drivers and FreeRTOS on a SAM E70 Xplained Ultra Evaluation Kit.	Link
4	DMA, QSPI	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	XDMAC with QSPI Application on a SAM E70 Xplained Ultra Evaluation Kit.	Link
5	TCP/ IP	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	File Transfer Protocol Application on a SAM E70 Xplained Ultra Evaluation Kit.	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following link:

• More application demonstrations on SAM E70 Xplained Ultra Evaluation Kit and other Development Boards/Kits having the same part number (ATSAME70Q21B)

4.1.7 SAM E70/S70/V70/V71 Reference Designs/Solutions

Table 4-6. SAM E70/S70/V70/V71 Reference Designs/Solutions

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	HMI Graphics	SAM E70 Xplained Ultra Evaluation Kit (DM320113)	Graphical User Interface Demonstrations: MPLAB Harmony v3 has various demonstration examples for creating an intuitive and reliable GUI in applications.	Reference design Link and Graphics demonstration link
2	Motor Control	dsPICDEM MCLV-3 Development Board High Voltage (DM330023-3) dsPICDEM MCLV-2 Development Board Low Voltage (DM330021-2) and ATSAME54 Motor Control Plugin Module (MA320207)	Motor Control for Appliances: There are multiple demonstration examples which are pre-configured to run on Microchip's various motor control development boards to make it easy to prototype a motor drive application.	Reference Design Link Motor Control examples

4.1.8 SAM E70/S70/V70/V71 Key Links

- SAM E70 Xplained Ultra Evaluation Kit (DM320113)
- SAM V71 Xplained Ultra evaluation Kit (ATSAMV71-XULT)
- MPLAB Harmony Landing Page.
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page



5. MIPS Family of Devices

5.1 PIC32MZ EF

Click on the following links to check the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/Solutions.

5.1.1 PIC32MZ EF Videos

Table 5-1. PIC32MZ EF Videos

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[®] X (IDE) How to Install MPLAB[®] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 4 and 5 for specific instructions using the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Device/Kit	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Explains how to create a simple application with the PIC32MZ EF using MPLAB Harmony v3. This application sends a "Hello World!" string to the PC terminal. MPLAB Harmony v3 is configurable through the MCC. Refer to items 4 and 5 for specific instructions using the MCC.	Create Your First Project with PIC32MZ EF using MPLAB [®] Harmony v3
3	Consumer	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Shows how to create a thermal camera heatmap application on the Curiosity PIC32MZ EF 2.0 Development board using the MCC.	Create a Thermal Camera Heatmap Application on the Curiosity PIC32MZ EF 2.0 Development Board
4	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [®] Code Configurator Content Manager
5	Getting Started with Software Tools	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to an MCC based project.	Getting Started with Harmony v3 Using Code Configurator
6	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package
7	Getting started with Solutions	N/A	Introduces the MPLAB Harmony Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package



5.1.2 PIC32MZ EF Training Modules

Table 5-2. PIC32MZ EF Training Modules

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/Kit	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Shows how to create an application to get started with the PIC32MZ EF using the MPLAB Harmony v3 software framework. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Peripheral Libraries on PIC32MZ EF MCUs
2	Getting Started with Device/Kit	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Shows how to create an application to get started with the PIC32MZ EF using the MPLAB Harmony v3 software framework drivers and middleware with FreeRTOS. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Drivers and Middleware on PIC32MZ EF MCUs using FreeRTOS
3	Getting started with tools	This training is using the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC
4	Migration	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC- based Project
5	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
6	Getting started with tools	N/A	Shows how to open an existing project, and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
7	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin, and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content

5.1.3 PIC32MZ EF Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications
- Class B Diagnostic Libraries For Functional Safety



5.1.4 PIC32MZ EF Technical Briefs

Table 5-3. PIC32MZ EF Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3259: This document explains how to create a simple application on PIC32 MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document is explained on one MCU. It can be ported for other MCUs. Note: Microchip is moving from the MHC to the MCC. Refer to items 4 and 5 in the Videos table.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Cache	TB3308: Handling Cache Coherency Issues at Runtime Using Cache Maintenance Operations on the PIC32MZ MCUs Using MPLAB Harmony v3	Link
9	DMA CRC	TB3196: How to Use the DMA CRC Generator on PIC32 Devices	Link
10	Getting Started	TB3296: Multiplexed and Remappable Functionalities on I/O pins on PIC32M Devices Using MPLAB Harmony v3	Link
11	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link

5.1.5 PIC32MZ EF Application Notes

Table 5-4. PIC32MZ EF Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Migration	AN3388: MPLAB Harmony v3 Application Development Guide for MPLAB Harmony v2 Users	Link
3	Bootloader	AN3703: Live Update Application on PIC32MZ MCUs Using MPLAB Harmony v3	Link

5.1.6 PIC32MZ EF Application Demonstrations

Table 5-5. PIC32MZ EF Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting started	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Getting Started Extended Application on a Curiosity PIC32MZ EF 2.0 Development Board.	Link
2	Datalogger, Automation	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Thermal Camera based Heat Map Application on a Curiosity PIC32MZ EF 2.0 Development Board + OLED C click + Grid-EYE click.	Link
3	Consumer, Graphics	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Snake Game Application on a Curiosity PIC32MZ EF 2.0 Development Board + High-Performance WVGA LCD Display Module with maXTouch Technology using Legato Graphics.	Link
4	IoT, Automation	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Wi-Fi [®] -based RGB LED Control Application on a Curiosity PIC32MZ EF 2.0 Development Board.	Link
5	Consumer, Audio	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	SD Card Audio Player Application on a Curiosity PIC32MZ EF 2.0 Development Board.	Link
6	Automation	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	EEPROM/Thumb drive Temperature Logger Application on a Curiosity PIC32MZ EF 2.0 Development Board.	Link



More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following link:

• More Application demonstrations on Curiosity PIC32MZ EF 2.0 Development Board and other Development Boards/Kits having the same part number (PIC32MZ2048EFM144)

5.1.7 PIC32MZ EF Reference Designs/Solutions

 Table 5-6.
 PIC32MZ EF Reference Designs/Solutions

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	HMI, Graphics	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Graphical User Interface Demonstrations: MPLAB Harmony v3 has various demonstration examples for creating an intuitive and reliable GUI in applications.	Reference design Link and Graphics demonstration link
2	Datalogger, Automation	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Thermal Camera Heat Map Demonstration Application	Link
3	IoT	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Wi-Fi [®] Remote Control for Lighting or Appliances Demonstration Application	Link
4	Consumer, Graphics	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Snake Game with Graphics Demonstration Application	Link
5	USB	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	USB Mass Storage Device for Multiple Drives Demonstration Application	Link
6	Consumer, Audio	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	SD Card/USB Audio Player Demonstration Application	Link
7	Consumer, Graphics	Curiosity PIC32MZ EF 2.0 Development Board (DM320209)	Audio Player/Recorder Demonstration Application	Link

5.1.8 PIC32MZ EF Key Links

- Curiosity PIC32MZ EF 2.0 Development Board (DM320209)
- MPLAB Harmony Landing Page
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page

5.2 PIC32MZ DA

Click on the following links to check the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/Solutions.



5.2.1 PIC32MZ DA Videos

Table 5-7. PIC32MZ DA Videos

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[*] X (IDE) How to Install MPLAB[*] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions for using the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with device/kit	PIC32MZ DA Curiosity Development Board (EV87D54A)	Introduces the PIC32MZ DA Curiosity Development Kit and explains how to create a simple application on Microchip's PIC32MZ DA, that is based on a MIPS Core 32-bit microcontroller using the MPLAB Harmony v3 MHC. Introduces the PIC32MZ DA Curiosity Development Kit and explains how to create a simple application on Microchip's PIC32MZ DA, that is based on a MIPS [™] Core 32-bit microcontroller using the MPLAB Harmony v3 MHC. MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions for using the MCC.	Getting Started with the PIC32MZ DA Curiosity Development Kit
3	Getting Started with S/W Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [®] Code Configurator Content Manager
4	Getting Started with S/W Tools	The video covers DM320209 and EV76S68A, the same content can be replicated for the PIC32MZ DA Curiosity Development Board (EV87D54A)	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to a MCC based project.	Getting Started with Harmony v3 Using Code Configurator
5	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package
6	Getting started with Solutions	N/A	Introduces the MPLAB Harmony Reference Apps package and describes its typical application types and download methods.	Harmony Reference Applications Package

5.2.2 PIC32MZ DA Training Modules

Table 5-8. PIC32MZ DA Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/ Kit	PIC32MZ DA Curiosity Development Board (EV87D54A)	Shows how to create an application to get started with PIC32MZ EF using the MPLAB Harmony v3 software framework. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC. The same training module example/ flow can be ported to the PIC32MZ DA following the same steps.	Getting Started with Harmony v3 Peripheral Libraries on PIC32MZ EF MCUs



•••••	continued				
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link	
2	Getting Started with Device/ Kit	PIC32MZ DA Curiosity Development Board (EV87D54A)	This training module shows how to create an application to get started with the PIC32MZ EF using the MPLAB Harmony v3 software framework drivers and middleware with FreeRTOS. The training module is based on the MHC, similar steps and flow can be used to create a project using the MCC. The same training module example or flow can be ported to the PIC32MZ DA following the same steps.	Getting Started with Harmony v3 Drivers and Middleware on PIC32MZ EF MCUs using FreeRTOS	
3	Getting started with tools	N/A	This training module shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC	
4	Getting started with tools	N/A	This training module shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project	
5	Getting started with tools	N/A	This page will show how to install the MPLAB [®] Code Configurator (MCC) plugin, and how to download MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content	
6	Getting started with tools	This training is uses the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	This tutorial shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC	
7	Migration	This training is uses the PIC32MZ EF. The same training can be used for other MCUs.	This tutorial shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC-based Project	

5.2.3 PIC32MZ DA Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB® Code Configurator (MCC) For Simplified Embedded Software Development
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications

5.2.4 PIC32MZ DA Technical Briefs

Table 5-9. PIC32MZ DA Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3259: This document explains how to create a simple application on a PIC32 MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document is explained on one MCU, it can be ported for other MCUs. Note: Microchip is moving from the MHC to the MCC. Refer to items 3 and 4 in the Videos table.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link



	continued		
Sl. No	Type/ Focus Area	Description	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS bBsed Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	Cache	TB3308: Handling Cache Coherency Issues at Runtime Using Cache Maintenance Operations on PIC32MZ MCUs Using MPLAB Harmony v3	Link
9	DMA CRC	TB3196: How to Use the DMA CRC Generator on PIC32 Devices	Link
10	Getting Started	TB3296: Multiplexed and Remappable Functionalities on I/O pins on PIC32M Devices Using MPLAB Harmony v3	Link
11	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link

5.2.5 PIC32MZ DA Application Notes

Table 5-10. PIC32MZ DA Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Migration	AN3388: MPLAB Harmony v3 Application Development Guide for MPLAB Harmony v2 Users	Link
3	Bootloader	AN3703: Live Update Application on PIC32MZ MCUs Using MPLAB Harmony v3	Link

5.2.6 PIC32MZ DA Application Demonstrations

Table 5-11. PIC32MZ DA Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting Started	PIC32MZ DA Curiosity Development Board (EV87D54A)	Getting Started Application with the PIC32MZ DA Curiosity Development Kit.	Link
2	Audio, Graphics	PIC32MZ DA Curiosity Development Board (EV87D54A)	SD Card USB Audio Player on a PIC32MZ DA Curiosity Development Kit + High-Performance 4.3" WQVGA Display Module with maXTouch [®] Technology using Legato Graphics.	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following link:

• More application demonstrations on PIC32MZ DA Curiosity Development Kit and other Development Boards/Kits having the same part number (PIC32MZ2064DAR176)

5.2.7 PIC32MZ DA Reference Designs/Solutions

Table 5-12. PIC32MZ DA Reference Designs/Solutions

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	HMI, Graphics	PIC32MZ DA Curiosity Development Board (EV87D54A)	Graphical User Interface Demonstrations: MPLAB Harmony v3 has various demonstration examples for creating an intuitive and reliable GUI in applications.	Ref design Link and Graphics demonstration link

5.2.8 PIC32MZ DA Key Links

- PIC32MZ DA Curiosity Development Board (EV87D54A)
- MPLAB Harmony Landing Page



- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs Repository
- Microchip Reference Designs Page

5.3 PIC32MK

Click on the following links to check the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.
- 7. Reference Designs/Solutions.

5.3.1 PIC32MK Videos

Table 5-13. PIC32MK Videos

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[*] X (IDE) How to Install MPLAB[*] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions to use the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with device/ kit	PIC32MK MCM Curiosity Pro Development Board(EV31E34A)	Introduces the PIC32 MK MCM Curiosity Pro Development Board and explains how to create a simple application on Microchip's PIC32 MK MCM 32-bit microcontroller using the MPLAB Code Configurator.	Getting Started on the PIC32MK MCM Curiosity Pro
3	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [*] Code Configurator Content Manager
4	Getting Started with Software Tools	The video covers DM320209 and EV76S68A. The same content can be replicated for the PIC32MK MCM Curiosity Pro Development Board (EV31E34A).	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to a MCC based project.	Getting Started with Harmony v3 Using Code Configurator
5	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package



5.3.2 PIC32MK Training Modules

Table 5-14. PIC32MK Training Modules

SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/ Kit	PIC32MK MCM Curiosity Pro Development Board (EV31E34A)	Shows how to create an application to get started with PIC32MK GP MCUs using the MPLAB Harmony v3 software framework. The training module is based on the MHC. Similar steps and flow can be used to create a project using the MCC. This training module is developed for PIC32MK GP Development Kit. The same flow can be reused for the PIC32MK MCM Curiosity Pro Development Board (EV31E34A).	Getting Started with Harmony v3 Peripheral Libraries on PIC32MK GP MCUs
2	Getting started with tools	N/A	Shows how to create a new MPLAB [*] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
3	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
4	Getting started with tools	N/A	Shows how to install the MPLAB [®] Code Configurator (MCC) plugin and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content
5	Getting started with tools	This training uses the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC
6	Migration	This training uses the PIC32MZ EF. The same training can be used for other MCUs.	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC- based Project

5.3.3 PIC32MK Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications
- Class B Diagnostic Libraries For Functional Safety



5.3.4 PIC32MK Technical Briefs

Table 5-15. PIC32MK Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3259: This document explains how to create a simple application on a PIC32 MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document explains one MCU, it can be ported for other MCUs. Note: Microchip is moving from the MHC to the MCC. Refer to items 3 and 4 in the Videos table.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	ADC	TB3319: How to Perform ADC Conversions with DMA Data Transfers on PIC32MK Devices Using MPLAB Harmony v3	Link
9	DMA CRC	TB3196: How to Use the DMA CRC Generator on PIC32 Devices	Link
10	Getting Started	TB3296: Multiplexed and Remappable Functionalities on I/O pins on PIC32M Devices Using MPLAB Harmony v3	Link
11	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link

5.3.5 PIC32MK Application Notes

Table 5-16. PIC32MK Application Notes

SI. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Migration	AN3388: MPLAB Harmony v3 Application Development Guide for MPLAB Harmony v2 Users	Link

5.3.6 PIC32MK Application Demonstrations

Table 5-17. PIC32MK Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting started	PIC32MK GP Development Kit (DM320106)	Getting Started Application Demonstration on a PIC32MK General Purpose (GP) Development Board using MPLAB Harmony v3	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following link:

• More application demonstrations on PIC32MZ MCM Curiosity Pro Development Board and other Development Boards/Kits having the same part number



5.3.7 PIC32MK Reference Designs/Solutions

Table 5-18. PIC32MK Reference Designs/ Solutions

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Motor Control	dsPICDEM MCLV-3 Development Board High Voltage (DM330023-3) dsPICDEM MCLV-2 Development Board Low Voltage (DM330021-2) and PIC32MK MCM Motor Control Plug In Module (MA320211) or PIC32MK1024 Motor Control Plug In Module (MA320024)	Motor Control for Appliances: There are multiple demonstration examples, which are preconfigured to run on the various motor control development boards, which makes it easy for prototyping motor drive applications.	Ref Design Link Motor Control examples

5.3.8 PIC32MK Key Links

- PIC32MK MCM Curiosity Pro Development Board (EV31E34A)
- PIC32MK MCA Curiosity Pro Development Board (EV15D86A)
- MPLAB Harmony Landing Page
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 GitHub Quick Docs repository
- Microchip Reference Designs Page

5.4 PIC32MX

Click on the following links to check the various collaterals:

- 1. Videos.
- 2. Training Modules.
- 3. Virtual/On-Demand Training.
- 4. Technical Briefs.
- 5. Application Notes.
- 6. Application Demonstrations.

5.4.1 PIC32MX Videos

Table 5-19. PIC32MX Videos

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Tools	N/A	 A step-by-step guide explaining: How to Install MPLAB[*] X (IDE) How to Install MPLAB[*] XC32 Compiler How to install the Configurator How to Download the Harmony Framework from the MPLAB Harmony v3 repository MPLAB Harmony v3 is configurable through the MCC. Refer to items 3 and 4 for specific instructions for using the MCC. 	How to Set-up the Tools Required to Get Started with Harmony v3
2	Getting Started with Software Tools	N/A	Explains how to use the MCC Content Manager.	MPLAB [®] Code Configurator Content Manager



•••••	continued			
SI. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
3	Getting Started with Software Tools	The video covers DM320209 and EV76S68A. The same content can be replicated for PIC32MX devices.	Explains how to create a new MPLAB Harmony v3 project using the MCC and shows how to migrate an MHC-based project to a MCC based project.	Getting Started with Harmony v3 Using Code Configurator
4	Getting started with Docs	N/A	Introduces the Quick Docs package to help develop applications using Microchip's 32-bit products using the MPLAB Harmony v3 software framework.	Harmony Quick Docs Package

5.4.2 PIC32MX Training Modules

Sl. No	Type/ Focus Area	Hardware Board/ Kit Used	Description	Link
1	Getting Started with Device/ Kit	Curiosity PIC32MX470 Development Board (DM320103)	Shows how to create an application to get started with the PIC32MX MCUs using the MPLAB Harmony v3 software framework. The training module is based on MHC. Similar steps and flow can be used to create a project using the MCC.	Getting Started with Harmony v3 Peripheral Libraries on PIC32MX 470 MCUs
2	Getting started with tools	N/A	Shows how to create a new MPLAB [®] Code Configurator (MCC) Harmony v3 project from scratch.	Create a new MPLAB Harmony v3 project using MCC
3	Getting started with tools	N/A	Shows how to open an existing project and use it with the MCC.	MCC - Open an Existing MPLAB [®] Harmony v3 Project
4	Getting started with tools	N/A	Shows how to install the MPLAB [*] Code Configurator (MCC) plugin, and how to download the MPLAB Harmony v3 framework.	MPLAB [®] Code Configurator Overview with MPLAB Harmony Content
5	Getting started with tools	This training uses the SAM D5x/E5x. The same training can be used as a reference for other MCUs.	Shows how to create a new MPLAB Harmony v3 project using the MCC.	Create a new MPLAB Harmony v3 project using MCC
6	Migration	This training uses the PIC32MZ EF. The same training can be used for other MCUs.	Shows how to update and configure an existing MPLAB Harmony Configurator (MHC)-based MPLAB Harmony v3 project to a MPLAB Code Configurator (MCC)-based project.	Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC- based Project

5.4.3 PIC32MX Virtual/On-Demand Training

More virtual trainings are available at Microchip University. Click on the following links for more details:

- Introduction To MPLAB[®] X IDE
- MPLAB[®] X Tips and Tricks
- Overview of the Microchip Code Configurator (MCC) Content Manager (CM)
- MPLAB[®] Code Configurator (MCC) For Simplified Embedded Software Development
- MPLAB[®] Harmony v3 Fundamentals
- Simple Applications Using the MPLAB[®] Harmony v3 Peripheral Libraries
- Creating Advanced Embedded Applications with 32-bit MCUs/MPUs using the MPLAB[®] Harmony v3 Software Framework
- FreeRTOS Simplified: A Beginner's Guide to Develop and Debug FreeRTOS Applications



5.4.4 PIC32MX Technical Briefs

Table 5-21. PIC32MX Technical Briefs

Sl. No	Type/ Focus Area	Description	Link
1	Getting Started	TB3259: This document explains how to create a simple application on a PIC32 MCU using the MPLAB Harmony v3 modules. This application sends a "Hello World!" string to a console running on a computer. This document is explained on one MCU. It can be ported for other MCUs. Note: Microchip is moving from the MHC to the MCC. Refer to items 3 and 4 in the Videos table.	Link
2	Getting Started	TB3232: This document explains how to set up the tools required to get started with the MPLAB Harmony v3 software development framework.	Link
3	Getting Started	TB3304: How to Add a New Configuration to an Existing MPLAB Harmony v3 Project	Link
4	Getting Started	TB3305: How to Use the MPLAB Harmony v3 Project Manifest Feature	Link
5	Getting Started	TB3290: MPLAB Harmony v3 Synchronous Drivers and Their Usage in FreeRTOS Based Applications	Link
6	Getting Started	TB3269: The Differences Between MPLAB Harmony v3 Synchronous and Asynchronous Drivers and When to Use Them	Link
7	Getting Started	TB3291: The Difference Between MPLAB Harmony v3 PLIBs and Drivers, and When to Use Them	Link
8	DMA CRC	TB3196: How to Use the DMA CRC Generator on PIC32 Devices	Link
9	Getting Started	TB3296: Multiplexed and Remappable Functionalities on I/O pins on PIC32M Devices Using MPLAB Harmony v3	Link
10	Getting Started	TB3253: How to Build an Application by Adding a New PLIB, Driver, or Middleware to an Existing MPLAB Harmony v3 Project	Link

5.4.5 PIC32MX Application Notes

Table 5-22. PIC32MX Application Notes

Sl. No	Type/ Focus Area	Description	Link
1	Migration	AN4495: MPLAB Harmony v3 Project Migration application note discusses the migration of an existing MPLAB Harmony v3 based project developed on a particular hardware (microcontroller or development board) platform to another one of Microchip's 32-bit hardware platforms of the user's choice.	Link
2	Migration	AN3388: MPLAB Harmony v3 Application Development Guide for MPLAB Harmony v2 Users	Link

5.4.6 PIC32MX: Application Demonstrations

Table 5-23. PIC32MX: Application Demonstrations

Sl. No	Туре	Hardware Board/ Kit Used	Description	Link
1	Getting started	Curiosity PIC32MX470 Development Board (DM320103)	Getting Started Application on a Curiosity PIC32MX470 Development Board	Link

More application demonstrations are available at Microchip's MPLAB Harmony GitHub repositories. Refer to the following link:

• More application demonstrations on Curiosity PIC32MX470 Development Board and other Development Boards/Kits having the same part number (PIC32MX470F512H)

5.4.7 PIC32MX Key Links

- Curiosity PIC32 MX470 Development Board
- MPLAB Harmony Landing Page
- MPLAB Harmony v3 GitHub Reference Application Repository
- MPLAB Harmony v3 Quick Docs GitHub Repository
- Microchip Reference Designs Page



6. **Revision History**

Revision A - June 2023

This is the initial public release of this document.

For access to previous non-public releases and other information regarding MPLAB Harmony v3, please contact a local Microchip sales representative.



Microchip Information

The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- Product Support Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- Business of Microchip Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Product Change Notification Service

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable". Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure



that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/ client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet- Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, Clockstudio, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, IntelliMOS, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, KoD, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, Trusted Time, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.



© 2023, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved.

ISBN: 978-1-6683-2710-4

Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.



Worldwide Sales and Service

MERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
orporate Office	Australia - Sydney	India - Bangalore	Austria - Wels
355 West Chandler Blvd.	Tel: 61-2-9868-6733	Tel: 91-80-3090-4444	Tel: 43-7242-2244-39
andler, AZ 85224-6199	China - Beijing	India - New Delhi	Fax: 43-7242-2244-393
l: 480-792-7200	Tel: 86-10-8569-7000	Tel: 91-11-4160-8631	Denmark - Copenhagen
ax: 480-792-7277	China - Chengdu	India - Pune	Tel: 45-4485-5910
echnical Support:	Tel: 86-28-8665-5511	Tel: 91-20-4121-0141	Fax: 45-4485-2829
ww.microchip.com/support	China - Chongqing	Japan - Osaka	Finland - Espoo
eb Address:	Tel: 86-23-8980-9588	Tel: 81-6-6152-7160	Tel: 358-9-4520-820
ww.microchip.com	China - Dongguan	Japan - Tokyo	France - Paris
tlanta	Tel: 86-769-8702-9880	Tel: 81-3-6880- 3770	Tel: 33-1-69-53-63-20
uluth, GA	China - Guangzhou	Korea - Daegu	Fax: 33-1-69-30-90-79
el: 678-957-9614	Tel: 86-20-8755-8029	Tel: 82-53-744-4301	Germany - Garching
ax: 678-957-1455	China - Hangzhou	Korea - Seoul	Tel: 49-8931-9700
ustin, TX	Tel: 86-571-8792-8115	Tel: 82-2-554-7200	Germany - Haan
el: 512-257-3370	China - Hong Kong SAR	Malaysia - Kuala Lumpur	Tel: 49-2129-3766400
oston	Tel: 852-2943-5100	Tel: 60-3-7651-7906	Germany - Heilbronn
estborough, MA	China - Nanjing	Malaysia - Penang	Tel: 49-7131-72400
el: 774-760-0087	Tel: 86-25-8473-2460	Tel: 60-4-227-8870	Germany - Karlsruhe
ax: 774-760-0088	China - Qingdao	Philippines - Manila	Tel: 49-721-625370
hicago	Tel: 86-532-8502-7355	Tel: 63-2-634-9065	Germany - Munich
asca, IL	China - Shanghai	Singapore	Tel: 49-89-627-144-0
el: 630-285-0071	Tel: 86-21-3326-8000	Tel: 65-6334-8870	Fax: 49-89-627-144-44
ax: 630-285-0075	China - Shenyang	Taiwan - Hsin Chu	Germany - Rosenheim
allas	Tel: 86-24-2334-2829	Tel: 886-3-577-8366	Tel: 49-8031-354-560
ddison, TX	China - Shenzhen	Taiwan - Kaohsiung	Israel - Ra'anana
el: 972-818-7423	Tel: 86-755-8864-2200	Tel: 886-7-213-7830	Tel: 972-9-744-7705
ax: 972-818-2924	China - Suzhou	Taiwan - Taipei	Italy - Milan
etroit	Tel: 86-186-6233-1526	Tel: 886-2-2508-8600	Tel: 39-0331-742611
ovi, MI	China - Wuhan	Thailand - Bangkok	Fax: 39-0331-466781
el: 248-848-4000	Tel: 86-27-5980-5300	Tel: 66-2-694-1351	Italy - Padova
ouston, TX	China - Xian	Vietnam - Ho Chi Minh	Tel: 39-049-7625286
el: 281-894-5983	Tel: 86-29-8833-7252	Tel: 84-28-5448-2100	Netherlands - Drunen
dianapolis	China - Xiamen		Tel: 31-416-690399
oblesville, IN	Tel: 86-592-2388138		Fax: 31-416-690340
el: 317-773-8323	China - Zhuhai		Norway - Trondheim
ax: 317-773-5453	Tel: 86-756-3210040		Tel: 47-72884388
el: 317-536-2380			Poland - Warsaw
os Angeles			Tel: 48-22-3325737
ission Viejo, CA			Romania - Bucharest
el: 949-462-9523			Tel: 40-21-407-87-50
x: 949-462-9608			Spain - Madrid
l: 951-273-7800			Tel: 34-91-708-08-90
aleigh, NC			Fax: 34-91-708-08-91
l: 919-844-7510			Sweden - Gothenberg
ew York, NY			Tel: 46-31-704-60-40
l: 631-435-6000			Sweden - Stockholm
an Jose, CA			Tel: 46-8-5090-4654
el: 408-735-9110			UK - Wokingham
el: 408-436-4270			Tel: 44-118-921-5800
anada - Toronto			Fax: 44-118-921-5820